

# TAMKO® TWM-I MASTIC

## Rubberized Bitumen Waterproofing Mastic

PRODUCT DATA

### DESCRIPTION

TAMKO TWM-1 is a high quality, trowel grade, rubberized bitumen mastic that dries to a durable but pliable seal allowing for minor expansion and contraction.

### USES

TAMKO TWM-1 has multiple uses including, sealing seams, overlaps, patches and terminations of the TAMKO Membrane.

### APPLICATION

Apply with a trowel or caulking gun

### COVERAGE RATES

Side laps: 900 lineal feet per gallon  
End laps: 600 lineal feet per gallon

### TYPICAL PHYSICAL PROPERTIES\*

Color	Black
Weight	9.29 lbs per gallon
Viscosity	
Brookfield 36 @ 20 rpm	<4000 poise
VOC	280 grams per liter
Flash Point	>100° F
Packaging	5 Gallon pails or 29 Ounce tubes

\*All values stated as nominal at time of manufacture.



Corporate	220 West 4th Street, Joplin, Missouri 64801
Central District	220 West 4th Street, Joplin, Missouri 64801
Northeast District	4500 Tamko Drive, Frederick, Maryland 21701
Southeast District	2300 35th Street, Tuscaloosa, Alabama 35401
Southwest District	7910 South Central Expressway, Dallas, Texas 75216
Western District	5300 East 43rd Avenue, Denver, Colorado 80216

800-841-1923  
800-641-4691  
800-368-2055  
800-228-2656  
800-443-1834  
800-530-8868

**TAMKO®**  
**WATERPROOFING**