



Manufacturer

American Gypsum
P.O. Box 90820
Albuquerque, NM 87199-0820
(800) 545-6302
FAX (505) 822-0578

09250-3

AQUABLOC (Green Board)

Product Description

American Gypsum Aquabloc Board is used as a water resistant base for application of ceramic or plastic tile. The use of a special wax emulsion compound in the gypsum core and application of a chemically treated face paper create a highly moisture resistant material. This green board is specially designed to minimize moisture problems in areas such as bathrooms, powder rooms, kitchens, and utility rooms.

Product Data

Typical Sizes:	1/2" thickness, 4' width, 8'-12' length 5/8" thickness, 4' width, 8'-12' length, Type X
Edges:	Tapered
Weight:	Approx. 1.8, and 2.2 lbs./sq.ft.
Compliance:	ASTM C-630 Flame Spread 20, Smoke Developed 0

Advantages

- Available in 1/2" thickness with regular core and 5/8" thickness with fire rated core.
- Noncombustible panels can be scored and sized for quick application.
- Installed over wood or metal framing.
- Panel edges are tapered for ease of finishing.
- Can be used in either residential or commercial applications.

Limitations

- Panel installation and finishing to comply with GA 216-96.
- Not recommended for gang showers or commercial food processing area subject to constant moisture.
- Panels should not be installed over a vapor retarder or on a wall acting as a vapor retarder.

Submittal Approvals: